

## Solid Rustic Carbonised **Strand Woven 135mm**

For commercial & residential use

## **Key Features**

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

## **Construction & Profile**

- Strand woven bamboo with a micro bevel and Uniclic® system on all 4 sides.



1850 x 135 x 14mm (1.5m<sup>2</sup> per pack)

## **Finish**

- 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

\* Residential structural warranty Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	BS 7976-2	PTV - 57
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2
Thermal Conductivity	-	0.16 W/(m K)

Narrant White Oak - 6.0 Jatoba - 10.5 Merbau - 8.6 Jarrah - 8.5 Janka Hardness Scale The higher the number, the harder the surface.

All measurements are shown in kilonewtons (kN)







The Bamboo Flooring Company Unit 5, Euston Street, Freemens Common, Leicester LE2 7ST Tel: 0116 2741050 Email: mail@bambooflooringcompany.com