

## Solid **Stone Grey Strand Woven 135mm**

WWW.BAMBOOFLOORINGCOMPANY.COM

For commercial & residential use



- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

## **Construction & Profile**

- Strand woven bamboo with a micro bevel and Uniclic® system on all 4 sides.



 $1850 \times 135 \times 14$ mm (1.5m<sup>2</sup> per pack)

## **Finish**

- Distressed finish with 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

\* Residential structural warranty Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	BS 7976-2	PTV - 63
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2
Thermal Conductivity	-	0.16 W/(m K)



**N55**Plus

product selector