

Solid Parquet Block Natural Strand Woven 90mm


For commercial & residential use

Key Features

- 100% renewable and sustainable Moso Bamboo monitored plantations
- Bamboo sourced from managed forests
- Extremely hard and stable with excellent indentation resistance
- Easy and quick to install Uniclic® locking system
- Compatible with wet under floor heating systems

Construction & Profile

- Strand woven bamboo with a micro bevel and Tongue & Groove profile



450 x 90 x 12mm (1.134m² per pack)


Finish

- 7 layers of Matt Bona Naturale lacquer. Coatings are water based, solvent-free and comply with European (E1) standards for off-gassing

* Residential structural warranty
Commercial structural 10 year warranty

Performance	Standard	Result
Flammability resistance	EN 13501-1:2007	Class Cf1-s1
Hardness	ASTM D1037 (Janka)	3562lbf (15.8kN)
Formaldehyde emissions	EN 717-1: 2004	0.080mg/m3 (E1)
Slip resistance	BS 7976-2	PTV - 57
Moisture content	-	8-10%
Density	EN 323: 1993	84-0 N/mm2
Thermal Conductivity	-	0.16 W/(m K)

25
YEAR
WARRANTY*



Strand Woven Bamboo - 15.8

Jatoba - 10.5

Merbau - 8.6

Jairah - 8.5

Maple - 6.4

Solid Bamboo - 6.2

White Oak - 6.0

Beech - 5.8

Janka Hardness Scale

The higher the number, the harder the surface.
All measurements are shown in kilonewtons (kN)

